



# R2416300UL AC Rack Mount CCTV Power Supply

Rev. DSR2416300UL\_09272011



R2416300UL

## **Overview**

This Altronix AC Rack Mount CCTV Power Supply provides 24VAC or 28VAC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- 115VAC, 50/60Hz, 3 amp.

### ***Output:***

- Sixteen (16) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) or 28VAC @ 10 amp (280VA) supply current.
- Outputs are rated @ 3.5 amp.
- Surge suppression.

### ***Visual Indicators:***

- Individual power LED indicators.

### ***Features:***

- Illuminated power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

### ***Features (cont'd):***

- Spare fuses provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Operating temperature: 0° C to 49° C ambient.
- Total system power consumption: 330 W.
- BTU/Hr.:
  - 24VAC: 114 BTU/Hr.
  - 28VAC: 106 BTU/Hr.
- System AC input VA requirement: 330 VA.
- Product weight (approx.): 17.2 lbs. (7.80 kg.)
- Shipping weight (approx.): 18.2 lbs. (8.26 kg.)

## **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions (H x W x D) (approximate):**  
 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)

