



R2416UL AC Rack Mount CCTV Power Supply

Rev. DSR2416UL_09272011



R2416UL

Overview

This Altronix AC Rack Mount CCTV Power Supply provides 24VAC or 28VAC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 3 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 7 amp (168VA) or 28VAC @ 6 amp (168VA) supply current.
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Visual Indicators:

- Individual power LED indicators.

Features:

- Illuminated power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

Features (cont'd):

- Spare fuses provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Operating temperature: 0° C to 49° C ambient.
- Total system power consumption: 175 W.
- BTU/Hr.:
 - 24VAC: 73 BTU/Hr.
 - 28VAC: 74 BTU/Hr.
- System AC input VA requirement: 175 VA.
- Product weight (approx.): 16.15 lbs. (7.33 kg.)
- Shipping weight (approx.): 17.15 lbs. (7.78 kg.)

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
 3.26" (83mm) x 19.125" (486mm) x 8.5" (216mm)

