



AL600ULPD4CBR

Overview

AL600ULPD4CBR is a multi-output power supply/charger that converts a 115VAC, 60Hz input into four (4) 12VDC or 24VDC Class 2 Rated power-limited outputs.

Specifications***Input:***

- Input 115VAC, 60Hz, 3.5 amp.

Output:

- 12VDC or 24VDC selectable output.
- 6 amp continuous supply current.
- Four (4) Class 2 Rated PTC protected power-limited outputs.
- Outputs are rated @ 2.5 amp.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.7 amp.

Supervision:

- AC fail supervision (form “C” contacts).
 - Notification trigger is selectable for 30 seconds (factory set) or 6 hours.
- Low battery supervision (form “C” contacts).
- Battery presence supervision (form “C” contacts).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 36.85 or 73.70 BTU/Hr.
- System AC input VA requirement: 402.5VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5” x 13” x 3.25” (342.9mm x 330.2mm x 82.55mm)
 - Accommodates two (2) 12VDC/7AH batteries.
- Product weight (approx.): 7.4 lbs. (3.36 kg).
- Shipping weight (approx.): 8.4 lbs. (3.81 kg).

Agency Approvals

UL 294 UL Listed for Access Control System Units.
UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



General Signaling Equipment
Evaluated to CSA Standard C22.2 No.205-M1983

Enclosure Dimensions (H x W x D approximate):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

