



**Altronix**<sup>®</sup>

## **ALTV2416CBX220** **AC CCTV Power Supply**

Rev. DSALTV2416CBX220\_12172012



ALTV2416CBX220

### **Overview**

ALTV2416CBX220 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via sixteen (16) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

#### ***Input:***

- 220VAC, 50/60Hz, 0.5 amp.

#### ***Output:***

- Sixteen (16) PTC protected outputs.
- 24VAC @ 7 amp (170VA) or 28VAC @ 6 amp (170VA) supply current.
- Outputs are rated @ 2.5 amp.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 85.99 BTU/Hr.
- System AC input VA requirement: 110VA.

#### ***Features:***

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Product weight (approx.): 14.33 lbs. (6.5 kg).
- Shipping weight (approx.): 15.21 lbs. (6.9 kg).

### **Agency Approvals**



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
**13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)**

