

**Overview**

ALTV2416X220 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications**Input:**

- 220VAC, 50/60Hz, 0.5 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 7 amp (170VA) or 28VAC @ 8 amp (170VA) supply current.
- Outputs are rated @ 3.5 amp.
- Sixteen (16) 1.56 amp isolated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 85.98 BTU/Hr.
- System AC input VA requirement: 110VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Product weight (approx.): 14.33 lbs. (6.5 kg).
- Shipping weight (approx.): 15.21 lbs. (6.9 kg).

Agency Approvals

Enclosure Dimensions (H x W x D approximate):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

