



**Altronix**<sup>®</sup>

## **ALTV615DC4220** **DC CCTV Power Supply**

Rev. DSALTV615DC4220\_01092015



ALTV615DC4220

### **Overview**

ALTV615DC4220 is designed with four (4) fuse protected outputs for powering CCTV cameras and other video accessories. It provides 6-15VDC distributed via four (4) outputs with a total of up to 2.5 amp continuous supply current.

### **Specifications**

#### ***Input:***

- 220VAC (working range 198VAC-256VAC), 50/60Hz, 0.5 amp.

#### ***Output:***

- Four (4) fuse protected outputs.
- 6VDC to 15VDC field adjustable.
- 2.5 amp total continuous supply current (*0.625 amp per device, 1 amp max.*).
- Outputs are rated @ 3.5 amp.
- Filtered and electronically regulated outputs.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 12.28-30.71 BTU/Hr.
- System AC input VA requirement: 110VA.

#### ***Features:***

- 230VAC grounded line installed.
- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
- Product weight (approx.): 8.55 lbs. (3.88 kg).
- Shipping weight (approx.): 9.05 lbs. (4.11 kg).

**Enclosure Dimensions** (*H x W x D approximate*):  
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

