



# ALTV615DC48ULM3

## UL Listed DC CCTV Power Supply

Rev. DSALTV615DC48ULM3 - 10222012



ALTV615DC48ULM3

### **Overview**

ALTV615DC48ULM3 provides 6VDC to 15VDC distributed via eight (8) Class 2 Rated fuse protected power-limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

### **Specifications**

#### **Input:**

- Input 115VAC, 50/60 Hz, 0.9 amp.

#### **Output:**

- Eight (8) Class 2 Rated fuse protected power-limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current  
(0.5 amp per device, 3.5 amp max.).
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

#### **Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- 12.28-30.71 BTU/Hr.
- System AC input VA requirement: 103.5VA.

#### **Features:**

- AC input and DC output LED indicators.
- Factory installed 3-wire line cord.
- Power ON/OFF switch.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### **Mechanical:**

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
8.5" x 7.5" x 3.75" (215.9mm x 190.5mm x 95.25mm)
- Product weight (approx.): 8.65 lbs. (3.92 kg.).
- Shipping weight (approx.): 9.15 lbs. (4.15 kg.).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.

**Enclosure Dimensions (H x W x D approximate):**  
 8.5" x 7.5" x 3.75" (215.9mm x 190.5mm x 95.25mm)

