



Overview

LPS5C12X linear power supply/charger converts a 115VAC 60Hz input to a 12VDC @ 3.5 amp continuous supply current. The output stays regulated until the battery discharges to 25% capacity.

Specifications

Input:

- 115VAC 50/60Hz rated @ 1.6 amp.

Output:

- 12VDC output.
- 3.5 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery:

- Battery leads included.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current 300mA.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- PTC battery protection.

Visual Indicators:

- AC/DC power LED indicator.

Supervision:

- Low battery and AC fail supervision (dry relay outputs 1 amp @ 28VDC).

Electrical:

- Operating temperature: -20° C to 49° C ambient.
- 21.49 BTU/Hr.

Mechanical:

- Enclosure dimensions:
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Enclosure:
 - Combination knockouts are 1/2" and 3/4".
 - Accommodates up to two (2) 12VDC/7AH batteries.
- Product weight (approx.): 11.4 lbs. (5.17kg).
- Shipping weight (approx.): 12.4 lbs. (5.62kg).

Enclosure Dimensions (H x W x D approximate):
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

