



LPS5C24X220

Overview

LPS5C24X220 linear power supply/charger converts a 220VAC 50/60Hz input to a 24VDC @ 3.5 amp continuous supply current. The output stays regulated until the batteries discharge to 25% capacity.

Specifications

Input:

- 220VAC 50/60Hz rated @ 0.8 amp.

Output:

- 24VDC output.
- 3.5 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery:

- Battery leads included.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current 300mA.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- PTC battery protection.

Visual Indicators:

- AC/DC power LED indicator.

Supervision:

- Low battery and AC fail supervision (dry relay outputs 1 amp @ 28VDC).

Electrical:

- Operating temperature: -20° C to 49° C ambient.
- 42.99 BTU/Hr.

Mechanical:

- Enclosure dimensions (H x W x D): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Enclosure:
 - Combination knockouts are 1/2" and 3/4".
 - Accommodates up to two (2) 12VDC/7AH batteries.
- Product weight (approx.): 11.1 lbs. (5.03kg).
- Shipping weight (approx.): 12.3 lbs. (5.58kg).

Enclosure Dimensions (H x W x D approximate):
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

