


AL600ULXB

Power Supply/Charger Board

Altronix AL600ULXB UL Listed Sub-Assembly power supply/charger converts a 115VAC, 60Hz input into a single 12VDC or 24VDC non power-limited output. It also offers a suite of features that includes AC fail supervision, battery presence, and low battery supervision.



AL600ULXB

Specifications

Input

Voltage	115VAC 60Hz, 3.5A max.
Fusing	5A / 250V

Output

Voltage	12VDC or 24VDC selectable
Current	6A continuous supply current
Other	Short circuit and thermal overload protection Filtered and regulated

Back-up Battery *(not included)*

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous

Supervision

AC Failure	Form "C" contacts
Battery	Form "C" contacts

Indicators (LED)

Input	115VAC is present
DC Output	Powered
Battery	Discharged or not connected

Agency Listings

UL:

UL294	Access Control
UL603	Burglar Alarm
UL1481	Fire Alarm

cUL:

Signal Equipment CSA C22.2 No.205-M1983

Physical and Environmental

Dimensions (L x W x H)

Board: 7.1" x 4.5" x 2" (180.3mm x 114.3mm x 50.8mm)
Shipping: 10" x 8" x 4" (254mm x 203.2mm x 101.6mm)

Weight (approx.)

Product Weight: 0.8 lb. (0.36 kg)
Shipping Weight: 0.95 lb. (0.43 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity

85% +/- 5%

BTU/Hr (approx.)

12VDC: 37 BTU/Hr.
24VDC: 74 BTU/Hr.

Mounting hardware included

Lifetime Warranty


AL600ULXB

Power Supply/Charger Board

Board Dimensions (L x W x H) and Drawing

7.1" x 4.5" x 2" (180.3mm x 114.3mm x 50.8mm)

Mounting Holes' Tolerance: +/- 0.04 in. (1mm)



Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com