

AL62424C

Linear Power Supply/Charger Kit

Altronix AL62424C linear power supply/charger kit has a wide range of applications including access control, security, and CCTV system accessories that require additional power. Kit includes: AL624 power supply, two (2) 12VDC/4AH rechargeable batteries, and 24VAC 40VA Class 2 Rated plug-in transformer.



AL62424C

Specifications

Input

Voltage 115VAC, 60Hz, 1.67A

Output

Voltage 24VDC

Current 0.75A supply current

Other Short circuit and thermal overload protection
Filtered and regulated

Battery Charging

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

Indicators (LED)

Input Input voltage is present

DC Output Powered

Physical and Environmental

Dimensions (L x W x H)

Board: 2.5" x 3" x 1.5" (63.5mm x 76.2mm x 38.1mm)

Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

Weight (approx.)

Product: 6.3 lb. (2.76 kg)

Shipping: 7.1 lb. (3.22 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)

Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.) 9 BTU/Hr.

Mounting hardware included

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com