

AL624TE220

Linear Power Supply/Charger Kit

Altronix AL624TE220 linear power supply/charger converts 220VAC input into 12VDC output. This general purpose power supply has a wide range of applications for access control, security and CCTV system accessories that require additional power.



AL624TE220

Specifications

Input

Voltage 220VAC (working range 198VAC-256VAC), 50/60Hz, 0.25A

Output

Voltage 12VDC
 Current 1.2A supply current
 Other Short circuit and thermal overload protection
 Filtered and regulated

Battery Charging

Type Sealed lead acid or gel type
 Failover Upon AC loss, instantaneous
 Batteries are sold separately

Indicators (LED)

Input Input voltage is present
 DC Output Powered

Physical and Environmental

Dimensions (H x W x D)

Enclosure:
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
 Shipping:
 13" x 10" x 7" (330.2mm x 254mm x 177.8mm)
 Enclosure accommodates two (2) 12VDC/4AH batteries
 or one (1) 12VDC/7AH battery

Weight (approx.)

Product: 4.6 lb. (2.1 kg)
 Shipping: 5.15 lb. (2.3 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
 Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity

85% +/- 5%

BTU/Hr (approx.):

7 BTU/Hr.

Mounting hardware is included

Lifetime Warranty


AL624TE220

Linear Power Supply/Charger Kit

Dimensions and Drawing

Dimensions (H x W x D approximate)

8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)



Lifetime Warranty