

ALTV1224C4220

AC/DC CCTV Power Supply

Altronix ALTV1224C4220 AC/DC Dual Output Power Supply is designed to provide both 12VDC and 24VAC outputs where a combination of both AC and DC outputs is required. It provides two (2) 12VDC outputs with a total current of 2A and two (2) 24VAC outputs with a total current of 4A.



ALTV1224C4220

Specifications

Input

Voltage 220VAC (working range 198VAC - 256VAC), 50/60Hz, 0.5A

Outputs

Voltage 12VDC and 24VAC simultaneous
 Current 2A total @ 12VDC and 4A total @ 24VAC
 Outputs Ratings AC fuses: 3.5A / 250VAC
 DC fuses: 1A / 250VAC

Indicators (LED)

Input 220VAC is present
 Output Output is powered

Physical and Environmental

Dimensions (H x W x D)

Enclosure: 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)
 Shipping: 15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)

Weight (approx.)

Product Weight 14.5 lb. (6.58 kg)
 Shipping Weight 15.4 lb. (7 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
 Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 72 BTU/Hr.

Lifetime Warranty