

# ALTV2432220 Series

## AC CCTV Power Supplies

Altronix ALTV2432220 series CCTV power supplies provide 24VAC or 28VAC distributed via thirty-two (32) fuse or PTC protected outputs for powering CCTV cameras, heaters, and other video accessories.



ALTV2432350220

### Key Features

- Thirty-two (32) fuse or PTC protected outputs
- 24VAC or 28VAC supply current
- Surge protection
- AC Power LED
- Illuminated power disconnect circuit breaker with manual reset
- Spare fuses provided (all models with primary and/or secondary fuses)
- CE European Conformity
- Lifetime Warranty

### ALTV2432220 Series Power Supply Configuration Reference Chart

Altronix Model Number	Output Voltage	Total Output Current (Power)	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)	220VAC 50/60Hz Input Current
ALTV2432220	24VAC	8A	32	-	✓	3.5A	1.5A
	28VAC	7A					
ALTV2432CB220	24VAC	8A		✓	-	2.5A	
	28VAC	7A					
ALTV2432350220	24VAC	14A		-	✓	3.5A	
	28VAC	12.5A					
ALTV2432350CB220	24VAC	14A		✓	-	2.5A	
	28VAC	12.5A					
ALTV2432600220	24VAC	28A		-	✓	3.5A	3A
	28VAC	25A					
ALTV2432600CB220	24VAC	28A		✓	-	2.5A	
	28VAC	25A					

#### Lifetime Warranty



# ALTV2432220 Series

AC CCTV Power Supplies

## Specifications

### Input

Voltage 220VAC (working range 198VAC - 256VAC), 50/60Hz

### Outputs

Voltage 24VAC or 28VAC  
Current Varies, see Reference Chart  
Protection Fused 3.5A / PTC 2.5A

### Indicators (LED)

Output 24VAC or 28VAC is present

### Agency Listings

CE European Conformity

## Physical and Environmental

### Dimensions (H x W x D)

Enclosure:  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)  
Shipping:  
15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)

### Weight (approx.)

Model	Product Weight	Shipping Weight
ALTV2432(CB)220	9.4 lb. (4.3 kg)	10.4 lb. (4.7 kg)
ALTV2432350(CB)220	15.9 lb. (7.2 kg)	16.9 lb. (7.7 kg)
ALTV2432600(CB)220	24.6 lb. (11.2 kg)	25.6 lb. (11.6 kg)

### Temperature

Operating: 0°C to 49°C (32°F to 120°F)  
Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/- 5%  
BTU/Hr. (approx.)

Model	24VAC	28VAC
ALTV2432(CB)220	98	100
ALTV2432350(CB)220	172	179
ALTV2432600(CB)220	344	358

## Lifetime Warranty