

ALTV615DC1016 Series

DC CCTV Power Supplies

Altronix ALTV615DC1016 Series power supplies are designed with sixteen (16) individual fuse or PTC protected outputs for powering CCTV cameras and other video accessories. They provide 6VDC-15VDC with a total of up to 10A continuous supply current.



ALTV615DC1016

Specifications

Input

Voltage 115VAC, 50/60Hz, 1.9A

Outputs

Voltage 6-15VDC

Current Up to 10A

Filtered and electronically regulated outputs
Short circuit and thermal overload protection

Indicators (LED)

Input LED

Output LED

Physical and Environmental

Dimensions (H x W x D)

Enclosure:

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)

Shipping:

15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)

Weight (approx.)

Product Weight: 14.9 lb. (6.76 kg)

Shipping Weight: 16.2 lb. (7.35 kg)

Temperature:

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 31-77 BTU/Hr., depending on output

ALTV615DC1016 Series Power Supply Configuration Reference Chart

| Altronix Model Number | Total Output Current (Power) | Output Voltage | Number of Outputs | PTC Protected Outputs (auto-resettable) | Fuse Protected Outputs | Output Current (max. per output) | 115VAC 50/60Hz Input Current |
|-----------------------|------------------------------|----------------|-------------------|---|------------------------|----------------------------------|------------------------------|
| ALTV615DC1016 | 10A | 6-15VDC | 16 | - | ✓ | 3.5A | 1.9A |
| ALTV615DC1016CB | | | | ✓ | - | 2.5A | |

Lifetime Warranty