

ALTV615DC4220

DC CCTV Power Supply

Altronix ALTV615DC4220 is designed with four (4) Class (2) Rated fuse protected outputs for powering CCTV Cameras and other video accessories. It provides 6-15VDC distributed via four (4) outputs with a total of up to 2.5A continuous supply current.



ALTV615DC4220

Specifications

Input

Voltage 220VAC (working range
198VAC - 256VAC), 50/60Hz, 0.5A

Outputs

Voltage 6 - 15VDC
Current Up to 2.5A
Ratings Fuses rated 1A/250V

Indicators (LED)

Input LED
Output LED

Physical and Environmental

Dimensions (H x W x D)

Enclosure:
8.5" x 7.5" x 3.875" (215.9mm x 191mm x 98.4mm)

Shipping:
13" x 10" x 7" (330.2mm x 254mm x 177.8mm)

Weight (approx.)

Product Weight: 3.4 lb. (1.54 kg)
Shipping Weight: 3.9 lb. (1.77 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 6 - 19 BTU/Hr., depending on output

Lifetime Warranty