

ALTV615DC4ULCB

DC CCTV Power Supply

Description

Altronix ALTV615DC4ULCB is designed with four (4) Class (2) Rated PTC protected power-limited outputs for powering CCTV Cameras and other video accessories. It provides 5.5-15VDC distributed via four (4) outputs with a total of up to 2.5A continuous supply current.



ALTV615DC4ULCB

Key Features

- Four (4) PTC protected power-limited outputs (auto-resettable).
- 5.5-15VDC field adjustable output voltage.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- AC Input and DC Output LED indicators.
- Power ON/OFF switch.
- Spare fuses provided.
- UL Listed in the U.S. and Canada.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

Specifications

Input

Voltage 24VAC/40VA or 24VAC/50VA from UL Listed Plug-in transformer.

Outputs

Voltage 5.5-15VDC.
 Current Up to 2.5A.
 Outputs Rating 2.5A/250VAC.

Indicators (LED)

Input LED.
 Output LED.

Agency Listings

Commercial CCTV Equipment UL2044
 Audio, Video and Similar Equipment CSA Standard C22.2
 No.1-98

CE European Conformity

Physical and Environmental

Dimensions (H x W x D):
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm).

Weight:

Product Weight 3.4 lbs. (1.54 kg).
 Shipping Weight 3.9 lbs. (1.77 kg).

Temperature:

Operating 0°C to 49°C (32°F to 120°F).
 Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 6 - 19 BTU/Hr., depending on output.