Altronix®

Rev. 05282026

BC400R

Power Supply/Battery Enclosure

Altronix BC400R is a UL Recognized NEMA 1 Rated power supply/battery enclosure that can accommodate a wide variety of Altronix power supplies, sub-assemblies, and accessories. Altronix enclosures feature ample knockouts that are suitable for 0.75" and 1" conduits.

For grey enclosure refer to model BC400

BC400R

BC400R with optional 12VDC/12AH batteries

Specifications

Features

- 18 Gauge steel enclosure
- Ample knockouts accommodating either 0.75" or 1" conduits for convenient access
- Includes camlock and two self-tapping screws to secure door

Capacity

- Enclosure accommodates up to two (2) 12VDC/12AH batteries

Agency Listings

Component Enclosure USR, CNR:

UL Recognized

Physical and Environmental

Dimensions (H x W x D)

Enclosure:

15.5" x 12.23" x 4.5" (393.7mm x 310.6mm x 114.3mm)

Shipping:

16.5" x 13.5" x 6" (419.1mm x 342.9mm x 152.5mm)

Weight (approx.)

Product:	7.8 lb. (3.54 kg
Shipping:	9.1 lb. (4.13 kg)

Accessories (order separately)



BCS4R

BCS4R

Red bracket fits BC400 enclosure to allow additional two (2) 12VDC/12AH batteries

Increases capacity to up to four (4) 12VDC/12AH batteries

For BC400R with BCS4R installed, order model BC400SR

BC400SR

WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively.

They accommodate standard zip ties or velcro straps.

These are ideal for wire management in our enclosures.

Mounting Magnet

MM4, MM8, MM12, MM24 - Magnetic Mounting Solution

Altronix mounting magnets accommodate screws and nylon standoffs to allow for mounting various boards/accessories in any metal enclosure or backplane.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Altronix®

BC400R

Power Supply/Battery Enclosure

Product Position Chart for the Following Models:

Power Supply/Chargers: AL300ULXB, AL400ULXB2, AL600ULXB, AL1012ULXB, AL1024ULXB2, eFlow3NB, eFlow4NB, eFlow6NB, eFlow102NB, eFlow104NB, eFlow15UB, Tango1B POE75, POE201, POE240, POE360, POE367, OLS75, OLS120, OLS120D2, OLS180, OLS200, OLS250, OLS350 *(220VAC Input power supply/chargers are also accommodated)* **Sub-Assemblies:** ACM8(CB), ACMS8(CB), ACMS12(CB), LINQ8ACM(CB)	A
AL175ULB, AL176ULB, AL201ULB, ACM4(CB), LINQ8PD(CB), MOM5, PD4UL(CB), PD8UL(CB), PDS8(CB), PDS16(CB), NetWay5A, NetWay5B, NetWay5BT(Q), NetWay5P(Q), NetWay5ES(Q), VR6, VR10	B



Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

BC400R

Power Supply/Battery Enclosure

Dimensions and Drawing

Dimensions (H x W x D approximate)

15.5" x 12.23" x 4.5" (393.7mm x 310.6mm x 114.3mm)



Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com