

## DPS5

### DIN Rail Mountable Linear Power Supply/Charger

Altronix DPS5 power supply/charger converts a low voltage AC input into a 6VDC, 12VDC or 24VDC output. This unit has a wide range of applications for access control, security and CCTV system accessories that require additional power.



DPS5

### Specifications

#### Input

Voltage 16VAC to 28VAC

#### Outputs

Voltage 6VDC, 12VDC or 24VDC selectable

Current 4A continuous max.

Other Short circuit and thermal overload protection  
Filtered and regulated

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

#### Indicators (LED)

Input Input voltage is present

DC Output Powered

#### Physical and Environmental

##### Dimensions (L x W x H)

3.5" x 3" x 2" (88.9mm x 76.2mm x 50.8mm)

Product Weight 0.35 lb. (0.16 kg)

Shipping Weight 0.5 lb. (0.23 kg)

##### Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

##### BTU/Hr (approx.):

6VDC: 12 BTU/Hr.

12VDC: 25 BTU/Hr.

24VDC: 49 BTU/Hr.

### Accessories:



ST3

#### ST3 - Snap Track (included)

Designed for mounting Altronix products to Din Rail without the use of mounting screws.



D10

#### D10 - Din Rail (order separately)

10" metal rail for mounting circuit boards and/or power supplies and peripherals inside equipment racks or enclosures.

#### Lifetime Warranty