

HubSat4WPV

Outdoor Passive UTP Transceiver Hub with Integral Camera Power

Altronix HubSat4WPV Outdoor Passive UTP Transceiver Hub with Integral Camera Power transmits UTP video, RS422/RS485 data, and power over a single CAT-5 or higher structured cable. Unit provides 4 camera channels in a weatherproof enclosure. Video transmission range is up to 228.6m (750 ft.) max. per channel. Units are compatible with AC and/or DC fixed or PTZ cameras when utilizing Altronix HubWayAv or HubWayDv Video Balun/Combiners. Unit also features 24VAC or 28VAC PTC protected outputs and surge suppression. Optionally, HubSat4WPV can be used as an accessory module to transmit video from up to 4 cameras over a single CAT-5 or higher structured cable back to the HubWay, HubWayLD or HubWayLDH Passive and Active UTP Transceiver Hubs. In addition, HubSat4WPV powers these cameras locally to eliminate the possibility of voltage drop associated with long cable runs.




HubSat4WPV

Specifications

Input

Voltage	220VAC (working range 198VAC - 256VAC), 50/60Hz, 0.7A
Fusing	3.5A/250V

Outputs

PTC protected outputs rated 1A per channel	
Voltage	Individually selectable 24VAC or 28VAC power outputs with OFF position
Current	Up to 1A max. per channel, not to exceed a total of 4A maximum current
Other	Surge suppression

Video

Four (4) channels of video over twisted pair up to a distance of 228.6m (750 ft.) per channel	
Four (4) 75 Ohm video outputs	

Data

RS422/RS485 data inputs	
-------------------------	--

Indicators (LED)

Outputs	Four (4) individual power LED indicators
---------	--

Agency Listings

CE	European Conformity
----	---------------------

Physical and Environmental

Enclosure Dimensions (H x W x D)	
12" x 8" x 6" (304.8mm x 203.2mm x 152.4mm)	
NEMA 4/IP 65 Rated outdoor enclosure	
Product Weight	13.75 lb. (6.24 kg)
Shipping Weight	15.1 lb. (6.85 kg)
Temperature	
Operating	0°C to 49°C (32°F to 120°F)
Storage	-20°C to 70°C (-4°F to 158°F)
Relative Humidity	85% +/-5%
BTU/Hr. (approx.):	
24VAC:	49 BTU/Hr.
28VAC:	57 BTU/Hr.

Lifetime Warranty

HubSat4WPV

Outdoor Passive UTP Transceiver Hub with Integral Camera Power



Accessories (order separately)



HubWayAv



HubWayAv2

HubWayAv and HubWayAv2

Video Balun/Combiners for use with 24VAC cameras

Compatible with all HubWay and HubSat UTP Transceiver Hubs.

Allow for video and data transmission and power over CAT-5 or higher structured cable to AC fixed cameras or PTZs.



HubWayDv

HubWayDv

Video Balun/Combiner for use with 12VDC cameras

Compatible with all HubWay and HubSat UTP Transceiver Hubs.

Allows for video and data transmission and power over CAT-5 or higher structured cable to 12VDC fixed cameras or PTZs.




HubWayDvi

HubWayDvi

Video Balun/Combiner for use with 12VDC cameras without isolation

Compatible with all HubWay and HubSat UTP Transceiver Hubs.

Allows for video and data transmission and isolated power over CAT-5 or higher structured cable to 12VDC fixed cameras or PTZs.



PMK1

PMK1 -

Pole Mount Kit

PMK1 pole mount kit is designed to simplify installation of outdoor units.

It accommodates 2" - 8" (diameter) poles.

Lifetime Warranty