Altronix®

Rev. 12012025

NetWay4E1BTWP3

4-Port Outdoor Hardened 4PPoE (802.3bt) Switch with Integral Power

Altronix NetWay4E1BTWP3 supports up to 90W per port (360W total power) for deploying the latest high-powered IP devices in remote locations. It is equipped with one (1) 1Gb SFP port to transmit data at long distances and four (4) 802.3bt compliant Ethernet ports. NetWay4E1BTWP3 accommodates single/multi-mode fiber to deliver data from NetWay Spectrum head-end media converters/injectors.

For managed switch see model NetWay4EBTWP3.

NetWay4E1BTWP3

Key Features

- Four (4) 10/100/1000 Mbps Ethernet ports rated at 90W each (limited to 360W total power)
- IEEE 802.3af, 802.3at, 802.3bt compliant
- One (1) Gigabit SFP port
- Built-in charger for sealed lead acid or gel type batteries
- CE European Conformity
- NEMA 4/4X, IP66-11 enclosure

Similar products

NetWay4E1BTWPX3	Outdoor 4-port Hardened 4PPoE Switch with Integral Power in NEMA 4/4X, IP66-11 enclosure which accommodates stand-by batteries
NetWay4E1BTX3	4-port Hardened 4PPoE Switch with Integral Power in NEMA 1 Rated indoor enclosure
NetWay4E1BTPL3	4-port Hardened 4PPoE Switch on a Backplane

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

NetWay4E1BTWP3

4-Port Outdoor Hardened 4PPoE (802.3bt) Switch with Integral Power

Typical Application



Accessories (order separately)



PMK1

PMK1 - Pole Mount Kit

PMK1 pole mount kit is designed to simplify installation of outdoor units. It accommodates 2"- 8"(diameter) poles.

SFP Modules - Hot Pluggable Transceivers

P1MM	Multi-Mode SFP Module for distances up to 550m
P1SM10	Single-Mode SFP Module for distances up to 10km
P1AB2K	Single Strand SFP Module for distances up to 2km
P1GCE	Copper SFP Module for distances up to 100m

NetWaySP1A

NetWaySP1A

Ethernet over Fiber Media Converter/Repeater for Applications Requiring an Additional SFP Port

NetWaySP1A PoE powered media converter/repeater converts 10/100/1000 Mbps to Fiber (1000Base-X/SX/LX).

Lock1WP

LOCK1WP - Pad Lock for Altronix Outdoor Enclosures

Altronix Lock1WP is a pad lock to secure the latches on Altronix outdoor enclosures. Includes a single pad lock and two (2) keys.

WG1

WG1 - NEMA Rated Wire Gland Inlet

Altronix WG1 facilitates wiring for all Altronix outdoor enclosures.

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

NetWay4E1BTWP3

4-Port Outdoor Hardened 4PPoE (802.3bt) Switch with Integral Power

Specifications

4-port PoE+ Hardened Switch (NetWay4E1BTB):

Input

Voltage	56VDC from POE360

Power Output

Maximum Power	Four (4) PoE ports rated at 90W each, 360W total power max. IEEE 802.3af (15W), IEEE 802.3at (30W), IEE 802.3bt (90W) compliant Integral surge protection
SFP Ports:	One (1) Gigabit SFP port
Ethernet Ports:	Four (4) 10/100/1000 Mbps ports Connectivity: RJ45, auto-crossover Wire type: 4-pair CAT5e or higher structured cable Speed: 10/100/1000 Mbps, half/full duplex, auto negotiation

Indicators (LED)

Individual **PoE On** LEDs for each port
Individual **IP Link status, 10/100Base-T/active** LEDs for each port
ALOS LED indicates fiber connection for SFP port
Heartbeat LED indicates proper operation of the unit

Power Supply/Charger (POE360):

Input

Voltage	115VAC, 60Hz, 3.5A or 230VAC, 50/60Hz, 2A
Input Fuse	5A/250V

Output

Voltage Range	54VDC/360W
Current	6.4A continuous supply current
Maximum Power	360W total power *(refer to operating temperature)* Integral surge protection

Battery Charging

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous
Charging Circuit	48VDC, 0.75A

Batteries are sold separately

NetWay4E1BTWP3:

Agency Listings

CE	European Conformity

Physical and Environmental

Dimensions (H x W x D)	
Enclosure:	13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)
Shipping:	20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

NEMA 4/4X, IP66-11 Rated enclosure for outdoor use

Weight (approx.)	
Product:	10.32 lb. (4.68 kg)
Shipping:	11.7 lb. (5.3 kg)
Temperature	
Operating:	
360W:	– 30ºC to 70ºC (– 22ºF to 158ºF)
240W:	– 30ºC to 75ºC (– 22ºF to 167ºF)
Storage:	– 30ºC to 85ºC (– 22ºF to 185ºF)
Relative Humidity	85% +/– 5%
BTU/Hr (approx.)	183 BTU/Hr.
Operating Altitude:	– 304.8 to 2,000m

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

NetWay4E1BTWP3

4-Port Outdoor Hardened 4PPoE (802.3bt) Switch with Integral Power

Dimensions and Drawing

Dimensions (H x W x D approximate)

13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)

FRONT VIEW



RIGHT SIDE VIEW



FRONT VIEW COVER REMOVED



END VIEW