Altronix®

Rev. 12222025

NetWay4E1X

4-port PoE+ Hardened Switch

Netway SPECTRUM

Altronix NetWay4E1X Indoor PoE+ Hardened Switch provides a 1Gb SFP port and four (4) PoE+ (30W) ports. Cameras/edge devices may be located up to 100m from the unit.

For unmanaged switch see model NetWay4EX.



NetWay4E1X

Key Features

- Four (4) 10/100/1000 Mbps PoE/PoE+ (up to 30W) ports
- IEEE 802.3af (15W) and IEEE 802.3at (30W) compliant
- 120W total power
- One (1) Gigabit SFP port
- Built-in charger for sealed lead acid or gel type batteries
- Automatic switch over to stand-by battery when AC fails
- PoE activity LED indicators
- CE European Conformity
- Lifetime Warranty

Similar products

NetWay4E1WPX	Outdoor 4-port PoE+ Hardened Switch in NEMA 4/4X, IP66-11 enclosure which accommodates stand-by batteries
NetWay4E1WP	Outdoor 4-port PoE+ Hardened Switch in NEMA 4/4X, IP66-11 enclosure
NetWay4E1WPN	Outdoor 4-port PoE+ Hardened Switch only in NEMA 4/4X, IP66-11 enclosure
NetWay4E1PL	4-port PoE+ Hardened Switch with Integral Power on a Backplane
NetWay4E1B	4-port PoE+ Hardened Switch (board only)

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

NetWay4E1X

4-port PoE+ Hardened Switch

Typical Application



Accessories (order separately)

SFP Modules - Hot Pluggable Transceivers

P1MM	Multi-Mode SFP Module for distances up to 550m
P1SM10	Single-Mode SFP Module for distances up to 10km
P1AB2K	Single Strand SFP Module for distances up to 2km
P1GCE	Copper SFP Module for distances up to 100m

NetWaySP1A

Ethernet over Fiber Media Converter/Repeater for Applications Requiring an Additional SFP (Fiber) Port

NetWaySP1A PoE powered media converter/repeater converts 10/100/1000 Mbps to Fiber (1000Base-X/SX/LX).

NetWay4E1X

4-port PoE+ Hardened Switch

Specifications

4-port PoE+ Hardened Switch (NetWay4E1B):

Input

Voltage	56VDC from POE201

Power Output

Maximum Power	Four (4) 10/100/1000 Mbps PoE/PoE+ (up to 30W) ports IEEE 802.3at (30W) and IEEE 802.3af (15W) compliant 120W total power Integral surge protection
Fiber Port:	One (1) Gigabit SFP port
Ethernet Ports:	Four (4) 10/100/1000 Mbps ports Connectivity: RJ45, auto-crossover Wire type: 4-pair CAT5 or better structured cable Distance: up to 100m Speed: 10/100/1000 Mbps, half/full duplex, auto negotiation

Indicators (LED)

Individual **PoE On** LEDs for each port
Individual **IP Link status, 10/100Base-T/active** LEDs for each port
ALOS LED indicates fiber connection for SFP port
Heartbeat LED indicates proper operation of the unit

Power Supply/Charger (POE201):

Input

Voltage	115VAC, 60Hz, 2.5A or 230VAC, 50/60Hz, 1.3A
Input Fuse	5A/250V

Output

Voltage	56VDC/120W
Current	2.2A continuous supply current
Maximum Power	120W total power Integral surge protection

Battery Charging

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous
Charging Circuit	48VDC, 0.75A

Batteries are sold separately

NetWay4E1X:

Agency Listings

CE	European Conformity

Physical and Environmental

Dimensions (H x W x D)	
Enclosure:	13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)
Shipping:	15" x 13.875" x 4.75" (381mm x 352.4mm x 120.6mm)
Weight (approx.)	
Product:	6.65 lb. (3.02 kg)
Shipping:	7.55 lb. (3.42 kg)
Temperature	
Operating:	
60W:	– 40ºC to 75ºC (– 40ºF to 167ºF)
75W:	– 40ºC to 70ºC (– 40ºF to 158ºF)
100W:	– 40ºC to 55ºC (– 40ºF to 131ºF)
120W:	– 40ºC to 45ºC (– 40ºF to 113ºF)
Storage:	– 40ºC to 85ºC (– 40ºF to 185ºF)
Relative Humidity	85% +/– 5%
BTU/Hr (approx.)	61 BTU/Hr.
Operating Altitude:	– 304.8 to 2,000m

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Altronix®

NetWay4E1X

4-port PoE+ Hardened Switch

Netway SPECTRUM

Dimensions and Drawing

Dimensions (H x W x D approximate)

13.5” x 13” x 3.25” (342.9mm x 330.2mm x 82.6mm)