

NetWay81GL

8-Port Hi-PoE Midspan Injector



Altronix NetWay81GL is an 8-port midspan in a 1U rack enclosure. It provides PoE/PoE+/Hi PoE (up to 60W power per port), and passes data at 10/100/1000 Mbps at distances up to 100m. Features also include an integral battery charger for applications requiring backup.




NetWay81GL

Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W) compliant
- Eight (8) ports for cameras/edge devices over ethernet
- Speed: 10/100/1000 Mbps
- 60W maximum power per port (not to exceed 240W)
- Port status LEDs
- Auto detection and protection of legacy non-PoE cameras/devices
- Built-in battery charger
- Lifetime Warranty

Typical Application



Lifetime Warranty

Specifications**Input**

115VAC, 60Hz, 3.25A or 230VAC, 50/60Hz, 2.0A

Power

Unit provides PoE / PoE+ / Hi PoE

60W max per port, not to exceed 240W total power

Ethernet

Connectivity: RJ45, auto-crossover

Wire type: 4-pair CAT5e or better structured cable

Distance: up to 100m

Speed: 10/100/1000 BaseT, half/full duplex, auto negotiation

Battery Charging

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

Batteries are sold separately. Separate enclosure is required

Indicators (LED)

Yellow and Green LED (by RJ45 jack):

IP Link status, 10/100/1000 Base-T/active

Green LED Port status

Physical and Environmental**Dimensions (H x W x D)**

Enclosure:

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

Shipping:

20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

Weight (approx.)

Product Weight: 6.17 lb. (2.8 kg)

Shipping Weight: 7.5 lb. (3.4 kg)

Temperature

Operating: - 20°C to 50°C (- 4°F to 122°F)

Storage: - 20° to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

Operating Altitude: Up to 2,000m

BTU/Hr. (approx.): 246 BTU/Hr

Accessories (order separately)**Repeaters:**

NetWayXT

**NetWayXT
PoE Repeater Module**

Extends data (video) for 100m



NetWayXTX

**NetWayXTX
PoE+ Repeater Module**

Extends data (video) for 100m

These repeaters will work if the Midspan is set for 15W or 30W, but not 60W.

Battery Backup:

RE2

RE2 – Rack Mount Battery Enclosure

Accommodates up to four (4) 12VDC/7AH batteries

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Dimensions and Drawing

Enclosure Dimensions (H x W x D approximate)

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)



Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com