

NetWaySP2PWP


3-Port Ethernet over Fiber PoE+ Hardened Switch

Altronix NetWaySP2PWP 3-Port PoE+ hardened switch with internal power converts a single Fiber (1000Base-X/SX/LX) into two (2) Ethernet ports (10/100/1000 Mbps) and provides PoE/PoE+ power to connected devices. Mounted in NEMA 4/4X, IP66-11 enclosure, it features auto detection and protection of legacy non-PoE cameras/devices.



Specifications -Input Features Auto detection and protection of legacy non-PoE cameras/devices. 115VAC, 60Hz, 2.5A or 230VAC, 50/60Hz, 1.3A. NEMA 4/4X, IP66-11 enclosure. Fiber Ports Lifetime Warranty One (1) 1Gb SFP port. Agency Listings **Output Power** CE European Conformity. Two (2) PoE / PoE+ ports, rated up to 30W max. IEEE 802.3af and IEEE 802.3at compliant. Physical and Environmental Dimensions (W x L x H) Ethernet 13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm) Connectivity: RJ45, auto-crossover. Weight (approx.) Wire type: 4-pair CAT5e. Product Weight: 10.5 lb. (4.76 kg). Distance: up to 100m. Shipping Weight: 11.9 lb. (5.4 kg). Speed: 10/100/1000 Mbps. Temperature Operating (30W): - 40°C to 70°C (- 40°F to 158°F) Indicators (LED) Storage: - 40°C to 75°C (- 40°F to 167°F). Yellow and Green LEDs: IP Link status. Relative Humidity: 85% +/- 5%. 10/100/1000 Base-T/active. Operating Altitude: - 304.8 to 2,000m. PoE present. Green PoE LEDs: Green SFP (Fiber) LEDs: SFP connection.

Typical Application



Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Rev. 11022021



NetWaySP2PWP

3-Port Ethernet over Fiber PoE+ Hardened Switch



Accessories (order separately) -



SFP Modules - Hot pluggable Transceivers

P1MM	Multi-Mode SFP Module for distances up to 550m.
P1SM10	Single-Mode SFP Module for distances up to 10km.
P1AB2K	Single Strand SFP Module for distances up to 2km.
P1GCE	Copper SFP Module for distances up to 100m.



PMK1 pole mount kit is designed to simplify installation of outdoor units. It accommodates 2"- 8"(diameter) poles.



PMK1

WG1 - NEMA Rated Wire Gland Inlets

WG1 facilitates wiring for all Altronix outdoor enclosures.