

OLS20E

Off-Line Switching Power Supply/Charger

Altronix OLS20E power supply/charger converts a 115VAC, 50/60Hz input into a 12VDC or 24VDC output. This unit has a factory installed 3-wire linecord. The OLS20E has a wide range of applications for access control and security system accessories that require additional power.



OLS20E

Specifications**Input**

Voltage 115VAC, 50/60Hz, 0.5A

Outputs

Voltage 12VDC or 24VDC selectable

Current 1A @ 12VDC or 0.5A @ 24VDC

Other Short circuit and thermal overload protection
Filtered and regulated

Back-up Battery *(not included)*

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

Indicators (LED)

Input Input voltage is present

DC Output Powered

Physical and Environmental**Dimensions (H x W x D)**

8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

Product Weight 3.3 lb. (1.50 kg)

Shipping Weight 4.3 lb. (1.95 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr (approx.): 6 BTU/Hr.

Lifetime Warranty