

RE2

Rack Mount Battery Enclosure

Altronix RE2 Rack Mount Battery Enclosure accommodates up to four (4) 12VDC/7AH batteries that can be connected in various configurations for either 12VDC or 24VDC applications.



Specifications

Features

- 19 Gauge black enclosure.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Quick connect terminals (wire gauge 14-20 AWG).

Agency Listings

- UL: UL 294 Access Control Unit Accessory Enclosure.
- cUL: cUL Listed For CSA Standard C22.2 No.205-M1983, Signal Equipment.
- CE European Conformity

Capacity

- Fits up to four (4) 12VDC/7AH batteries.

Dimensions (H x W x D)

3.2" x 19.0" x 8.4" (81.3mm x 482.6mm x 213.6mm).

Product Weight 10.4 lbs. (4.72 kg).

Shipping Weight 12.9 lbs. (5.85 kg).

Accessories (order separately)



BT126

BT126 - Rechargeable Battery,

Sealed lead acid (SLA) battery supplies 12VDC/7AH for security, access, surveillance and fire applications.

Dimensions and Drawing

Dimensions (H x W x D approximate)

3.2" x 19.0" x 8.4" (81.3mm x 482.6mm x 213.6mm)

