

Isolated Series

AC CCTV Rack Power Supplies

Altronix Isolated Series Rack Mount CCTV Power Supplies provide 24VAC distributed via multiple fuse or PTC protected isolated outputs for powering CCTV cameras, heaters, and other video accessories.



R248ULi

Key Features

- Eight (8) or sixteen (16) fuse or PTC protected outputs
- 24VAC isolated outputs
- Surge protection
- Individual power LED indicators
- Illuminated power disconnect circuit breaker with manual reset
- Removable terminal blocks with locking screw flanges.
- Spare fuses provided (all models with primary and/or secondary fuses)
- UL Listed in the U.S. and Canada
- CE European Conformity
- Lifetime Warranty

Isolated Series Power Supply Configuration Reference Chart

Altronix Model Number	115VAC 50/60Hz Input Current	Output Voltage (VAC)	Total Output Current (Power)	Number of Outputs	PTC Protected Power-Limited Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)	Primary In-line Fuse Ratings
R248ULi	2.7A	24VAC	12.5A (300VA)	8	—	✓	1.56A	5A/ 250V
R248ULCBi		24VAC	12.5A (300VA)		✓	—		
R2416ULi*	5.4A	24VAC	25A (600VA)	16	—	✓		
R2416ULCBi*		24VAC	25A (600VA)		✓	—		

*Outputs 1-8 provide 12.5A (300VA) max. Outputs 9-16 provide 12.5A (300VA) max.

Lifetime Warranty



Isolated Series

AC CCTV Rack Power Supplies

Specifications

Input

Voltage	115VAC, 50/60Hz
Fusing	5A/250V

Outputs

Voltage	24VAC
Current	1.56A
Protection	Fused 3.5A / PTC 2.5A

Indicators (LED)

Output	Eight (8) or sixteen (16) individual LEDs
--------	---

Agency Listings

UL2044	Commercial CCTV Equipment
CSA Standard C22.2 No.1-98	Audio, Video and Similar Equipment
CE	European Conformity

Physical and Environmental

2U rack mount chassis for use in standard EIA 19" rack.

Dimensions (H x W x D):

Enclosure:

3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

Shipping:

20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

Weight (approx.):

Model	Product Weight	Shipping Weight
R248UL(CB)i	17.2 lb. (7.80 kg)	18.2 lb. (8.26 kg)
R2416UL(CB)i	24.4 lb. (11.07 kg)	25.4 lb. (11.52 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)

Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.):

Model	BTU/Hr.
R248UL(CB)i	114
R2416UL(CB)i	227

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com