

Isolated Series AC CCTV Rack Power Supplies

Description

Altronix Isolated Series Rack Mount CCTV Power Supplies provide 24VAC distributed via multiple fuse or PTC protected isolated outputs for powering CCTV cameras, heaters, and other video accessories.



R248ULi

Key Features

- Eight (8) or sixteen (16) fuse or PTC protected outputs.
- 24VAC isolated outputs.
- Surge protection.
- Individual power LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Removable terminal blocks with locking screw flanges.
- Spare fuses provided (all models with primary and/or secondary fuses).
- CE Approved.
- Lifetime Warranty

Isolated Series Power Supply Configuration Reference Chart

Altronix Model Number	Output Voltage (VAC)	Total Output Current (Power)	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)	Primary In-line Fuse Ratings	220VAC 50/60Hz Input Current
R248i220	24VAC	12.5A (300VA)	8	-	✓	1.75A	5A/250V	1.4A
R248CBi220		12.5A (300VA)		✓	-			
R2416i220*		25A (600VA)	16	-	✓			2.7A
R2416CBi220*		25A (600VA)		✓	-			

*Outputs 1-8 provide 12.5A (300VA) max. Outputs 9-16 provide 12.5A (300VA) max.

Isolated Series AC CCTV Rack Power Supplies



Specifications

Input

Voltage 220VAC (working range 198VAC - 256VAC),
50/60Hz.
Fusing 5A/250V.

Outputs

Voltage 24VAC.
Current 1.56A.
Protection Fused 3.5A / PTC 2.5A.

Indicators (LED)

Output Eight (8) or sixteen (16) individual LEDs.

Agency Listings

CE European Conformity

Physical and Environmental

2U rack mount chassis for use in standard EIA 19" rack.

Dimensions (H x W x D):

3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm).

Weight:

Model	Product Weight	Shipping Weight
R248(CB)i220	17.2 lbs. (7.80 kg)	18.2 lbs. (8.26 kg)
R2416(CB)i220	24.4 lbs. (11.07 kg)	25.4 lbs. (11.52 kg)

Temperature:

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/- 5%.

BTU/Hr. (approx.):

Model	BTU/Hr.
R248(CB)i220	114
R2416(CB)i220	227