

ReServ2WPV Video Surveillance UPS

Description

Altronix ReServ2WPV Outdoor Video Surveillance UPS is designed to provide power for 24VAC cameras during normal or power outage conditions. True sine wave regulated AC outputs.



ReServ2WPV

Specifications

Input

Voltage 230VAC, 60Hz, 3.5A.

Outputs

16 individual PTC protected power-limited auto-resettable outputs rated 1A each.

Voltage 24VAC.

Current 4A (0.25A per device, 1A max.)
(Ambient Temperature -33°C to 30°C).
3.5A (0.21A per device, 1A max.)
(Ambient Temperature -33° to 42° C).

Other Short circuit and thermal overload protection.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

Supervision

AC Failure Form "C" contacts.

Low Battery Form "C" contacts.

Indicators (Audio and LED)

Input Input voltage is present.

DC Output Powered.

Outputs Individual Indicators.

Audio AC Fail and Battery Fail.

Agency Listings

CE European Conformity.

Physical and Environmental

Dimensions (H x W x D)

17.53" x 15.3" x 6.67" (445.3mm x 388.6mm x 169.4mm).
Enclosure accommodates up to two (2) 12VDC/12AH batteries.
NEMA4 / IP66 Rated Enclosure.

Product Weight 14 lbs. (6.35 kg).

Shipping Weight 15.5 lbs. (7.1 kg).

Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 49 BTU/Hr.

Accessories

PMK2 Pole Mount Kit (order separately)

PMK2 pole mount kit is designed to simplify installation of outdoor units.

It accommodates 2" - 8" (diameter) poles.

Kit includes:

- Two (2) powder coated steel mount brackets.
- Four (4) stainless steel bolts.
- Four (4) stainless steel lock washers.
- Two (2) wormgear quick release straps.



PMK2