

ReServ3

Video Surveillance UPS

Description

Altronix ReServ3 Video Surveillance UPS is designed to provide power for 12VDC cameras during normal or power outage conditions. Regulated DC outputs.



ReServ3
(order batteries separately)

Specifications

Input

Voltage 115VAC, 60Hz, 3.5A.

Outputs

16 individual PTC protected power-limited auto-resettable outputs rated 1A each.

Voltage 12VDC.

Current 8A (0.66A per device, 1A max.)
(Ambient Temperature -33°C to 30°C).

Other Short circuit and thermal overload protection.

Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

Supervision

AC Failure Form "C" contacts.

Low Battery Form "C" contacts.

Indicators (Audio and LED)

Input Input voltage is present.

DC Output Powered.

Outputs Individual Indicators.

Audio AC Fail and Battery Fail.

Agency Listings

UL/cUL UL60950-1 (Information Technology).

CE European Conformity.

Physical and Environmental

Dimensions (H x W x D)

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

Enclosure accommodates up to two (2) 12VDC/7AH batteries.

Product Weight 10.36 lbs. (4.7 kg).

Shipping Weight 11.26 lbs. (5.11 kg).

Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 49 BTU/Hr.