

# ReServ3V

## Video Surveillance UPS

### Description

Altronix ReServ3V Video Surveillance UPS is designed to provide power for 12VDC cameras during normal or power outage conditions. Regulated DC outputs.



ReServ3V  
(order batteries separately)

### Specifications

#### Input

Voltage 230VAC, 50/60Hz, 2.0A.

#### Outputs

16 individual PTC protected power-limited auto-resettable outputs rated 1A each.

Voltage 12VDC.

Current 8A (0.66A per device, 1A max.)  
(Ambient Temperature -33°C to 30°C).

Other Short circuit and thermal overload protection.

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type.

Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.

Low Battery Form "C" contacts.

#### Indicators (Audio and LED)

Input Input voltage is present.

DC Output Powered.

Outputs Individual Indicators.

Audio AC Fail and Battery Fail.

#### Agency Listings

CE European Conformity.

#### Physical and Environmental

##### Dimensions (H x W x D)

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

Enclosure accommodates up to two (2) 12VDC/7AH batteries.

Product Weight 10.36 lbs. (4.7 kg).

Shipping Weight 11.26 lbs. (5.11 kg).

##### Temperature

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 49 BTU/Hr.