Altronix®

Rev. 08022022

T1RAL3316

Rack Access and Power Integration Solution

TROVE™

Altronix T1RAL3316 Trove™ Rack kit is pre-assembled and consists Trove1R enclosure and TAL1R Altronix backplane with two (2) 12VDC or 24VDC @ 6A power supply/chargers and two (2) eight (8) output fused dual output access control modules. Trove simplifies board layout and wire management, reduces installation time and labor costs.



T1RAL3316

Key Features

- Output Power:
  - Sixteen (16) individully selectable 12VDC or 24VDC fused lock power outputs rated at 12A total max.
    - Fire Alarm Disconnect is individually selectable by output
- Power status LED on front panel
- Includes cam lock, tamper switch and mounting hardware
- Simplified board layout and wire management
- 6' IEC320 3-wire power cord
- 2U drawer on extendable rails
- Black powder coated steel enclosure
- Convenient knockout configuration:
  - Four (4) double knockouts - 3/4" Conduit and 1" Conduit
  - Two (2) double knockouts - 1/2" Conduit and 3/4" Conduit
- Included Z Bracket facilitates ease of wiring
- CE European Conformity
- Lifetime Warranty*

**Altronix Power Supply/Charger and Sub-Assemblies only*

Accessories (order separately)



RE2

RE2 - Rack Mount Battery Enclosure
accommodates up to four (4) 12VDC/7AH batteries



WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts
Altronix WM5, WM25, and WM100 are packs of
5, 25 or 100 magnetic cable tie mounts respectively.
They accommodate standard zip ties or velcro straps.
These are ideal for wire management in our Trove series.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

T1RAL3316

Rack Access and Power Integration Solution

Specifications

Two (2) Power Supply/Chargers (AL600RLB):

Input

Voltage	115VAC, 60Hz, 3.5A max.
Input Fuse	5A/250V

Output

Voltage	12VDC or 24VDC selectable
Current	6A @ 12VDC or 24VDC continuous max.
Other	Overvoltage protection Filtered and regulated

Battery Charging

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous

Batteries are sold separately

Supervision

AC Failure	Form “C” contacts
Battery	Form “C” contacts

Indicators (LED)

Input	115VAC is present
DC Output	Powered
Battery	Discharged or not connected

Two (2) Dual InputAccess Power Controllers (ACMS8):

Input

Voltage	24VDC from one AL600RLB and 12VDC from another
Input Fuses	15A/32V

Outputs

Voltage: 12 or 24VDC individually selectable.

Eight (8) selectable 12VDC - 24VDC independently controlled outputs or eight (8) indepently controlled Form “C” relay outputs:

a) Fail-Safe and/or Fail-Secure power outputs
b) Form “C” Relays. 28VAC or VDC @ 2.5A Rated
c) Auxiliary power outputs (unswitched)
d) Any combination of the above

Any of the eight (8) fuse protected power outputs are selectable to follow power Input 1 or Input 2

Individual outputs may be set to OFF position for servicing

Output Fuses: 3A/32V

Indicators (LED)

Red LEDs	Outputs are triggered (relays energized)
Blue LED	FACP disconnect is triggered

Individual voltage LEDs

Green:	12VDC
Red:	24VDC

T1RAL3316 Kit:

Agency Listings

CE	European Conformity

Physical and Environmental:

Dimensions (H x W x D):

Modular 2U standard EIA 19” rack mount chassis
Enclosure: 3.25” x 19.0” x 26.5” (82.6mm x 482.6mm x 673.1mm)
Shipping: 31” x 23” x 8.25” (787.4mm x 584.2mm x 209.6mm)

Weights (approx.):

Product:	23 lb. (10.4 kg)
Shipping:	26.6 lb. (12.1 kg)


Temperature

Operating:	0ºC to 49ºC (32ºF to 120ºF)
Storage:	– 20ºC to 70ºC (– 4ºF to 158ºF)
Relative Humidity	85% +/– 5%
BTU/Hr.:	172 BTU/Hr.

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

T1RAL3316

Rack Access and Power Integration Solution



Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com


T1RAL3316

Rack Access and Power Integration Solution

Dimensions and Drawing

Dimensions (H x W x D approximate)

3.25” x 19.0” x 26.5” (82.6mm x 482.6mm x 673.1mm)



Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com