

T1SFK38S (Kit)

Access & Power Integration Solution for Swiftlane



Altronix T1SFK38S kit consists of Trove1 enclosure, TSF1 Altronix/Swiftlane Controls backplane with one (1) 12VDC or 24VDC @ 6A power supply/charger 12VDC voltage regulator, eight (8) fuse protected output dual voltage power distribution module. This kit also accommodates one (1) Swiftlane Controls Door Controller 5 (SL-DCU-5) board. Trove simplifies board layout and wire management, reduces installation time and labor costs.



T1SFK38S

Swiftlane boards are not included

Key Features

- | | |
|--|---|
| <ul style="list-style-type: none"> - 12VDC or 24VDC power supply/charger - Accommodates one (1) Swiftlane Controls Door Controller 5 (SL-DCU-5) board - Convenient knockout configuration: <ul style="list-style-type: none"> - One (1) double knockout 1.948" (1-1/2" Conduit) - Nine (9) double knockouts 1.362" (1" Conduit) / 1.115" (3/4" Conduit) - 16 AWG galvanized steel backplane simplifies board layout and wire management - Enclosure accommodates up to two (2) 12VDC/7AH batteries | <ul style="list-style-type: none"> - Supervision <ul style="list-style-type: none"> - AC Fail - Low Battery and Battery Presence - Low power shutdown - Agency Listings: <ul style="list-style-type: none"> - All Altronix components of this Trove kit are UL Listed sub-assemblies. Please refer to the Sub-Assembly Installation Guides for further information - UL: UL294 - Access Control System - cUL: CAN/ULC - s319-05 - Electronic Access Control Systems - CE European Conformity - Lifetime Warranty* |
|--|---|

**Altronix Power Supply/Chargers and Sub-Assemblies only*

Accessories (order separately)



WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively. They accommodate standard zip ties or velcro straps. These are ideal for wire management in our Trove series.



Mounting Magnet

MM4, MM8, MM12, MM24 - Magnetic Mounting Solution

Altronix mounting magnets accommodate screws and nylon standoffs to allow for mounting various boards/ accessories in any metal enclosure or backplane.

Specifications

Power Supply (AL600ULXB):

Input

Voltage	115VAC, 60Hz, 3.5A max.
Fusing	5A / 250V.

Output

Voltage	12VDC or 24VDC selectable
Current	6A @ 12VDC or 24VDC continuous max.
Other	Overvoltage protection Filtered and regulated

Battery Backup

Capacity	7AH/12VDC (Up to 2 within enclosure) 40AH/65AH (requires separate enclosure)
Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous

Supervision

AC Failure	Form "C" contacts
Battery	Form "C" contacts

Indicators (LED)

Input	115VAC is present
DC Output	Powered
Battery	Discharged or not connected

Dual Input Power Distribution Module (PDS8)

Input

Voltage	24VDC from AL600ULXB and 12VDC from VR6
Input Fuse	10A/32V

Outputs

Voltage	12VDC and/or 24VDC
Any of the eight (8) power outputs are selectable to follow power Input 1 or Input 2	
Individual outputs may be set to OFF position for servicing	

Outputs Ratings

Fuses	3A/32V
-------	--------

Indicators (LED)

DC Output	Eight (8) individual output LEDs
Green:	12VDC
Red:	24VDC

Voltage Regulator (VR6):

Input

Voltage	24VDC from AL600ULXB
---------	----------------------

Output

Voltage	12VDC
Current	6A continuous
Other	Surge suppression

Indicators (LED)

Input	24VDC is present
Output	Powered

T1SFK38S Kit:

Agency Listings

All components of this Trove kit are UL Listed sub-assemblies. Please refer to the corresponding Sub-Assembly Installation Guides for further information

CE European Conformity

Physical and Environmental

Dimensions (H x W x D)

Enclosure:	18" x 14.5" x 4.62" (457.2mm x 368.3mm x 118.0mm)
Shipping:	21.75" x 18.25" x 5.75" (552.5mm x 463.6mm x 146.1mm)

Weight (approx.)

Product	15.5 lb. (7.0 kg)
Shipping	19.5 lb. (8.9 kg)

Temperature

Operating	0°C to 49°C (32°F to 120°F)
Storage	- 20°C to 70°C (- 4°F to 158°F)


Relative Humidity

85% +/- 5%

BTU/Hr (approx.):

12VDC:	40 BTU/Hr
24VDC:	77 BTU/Hr

Access Controller Position Chart for Swiftlane Controls Door Controller 5 (SL-DCU-5):





SWIFTLANE

T1SFK38S (Kit)

Access & Power Integration Solution for Swiftlane

Altronix

TRIVE

Dimensions and Drawing

Dimensions (H x W x D approximate)

18" x 14.5" x 4.62" (457.2mm x 368.3mm x 118.0mm)

