

TM400K6 (Kit)

Access & Power Integration Solution for Mercury

Altronix TM400K6 consists of TM400 enclosure with 12VDC or 24VDC (factory set at 24VDC) @ 4A power supply/charger and eight (8) fuse protected output power distribution module. This kit also accommodates various combinations of Mercury* boards for up to two (2) doors in a single enclosure. Trove simplifies board layout and wire management, reduces installation time and labor costs.

***Also compatible with these authentic Mercury partners:**

AccessNsite, Avigilon, BadgePass, BluBox, Feenics, Genetec, Identocard, IMRON, Johnson Controls, Kastle, Keri Systems, Lenel/S2, LockState, Maxxess, Midpoint Security, NLSS, Open Options, Panasonic Video Insight, Quintron, RS2, Schneider Electric, Vanderbilt



TM400K6

Mercury boards are not included

Key Features

- 12VDC or 24VDC power supply/charger
- Accommodates the following Mercury controllers: MR50, LP1502, LP4502, MR52, MR16IN, MR16OUT
- Convenient knockout configuration:
 - Twelve (12) double knockouts
 - 1.125" (3/4" Conduit) / 1.375" (1" Conduit)
- 16 gauge black enclosure simplifies board layout and wire management
- Enclosure accommodates up to two (2) 12VDC/7AH batteries
- Supervision
 - AC Fail
 - Low Battery and Battery Presence
 - Low power shutdown
- CE European Conformity
- Lifetime Warranty*

**Altronix Power Supply/Chargers and Sub-Assemblies only*

Accessories (order separately)



LINQ2

LINQ2 - Network Supervision

Altronix LINQ2 Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Reports system diagnostics via Email



WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively. They accommodate standard zip ties or velcro straps. These are ideal for wire management in our Trove series.



Mounting Magnet

MM4, MM8, MM12, MM24 - Magnetic Mounting Solution

Altronix mounting magnets accommodate screws and nylon standoffs to allow for mounting various boards/ accessories in any metal enclosure or backplane.

Specifications**Power Supply (eFlow4NB):****Input**

Voltage	120VAC, 60Hz, 3.5A
Input Fuse	5A/250V

Output

Voltage	24VDC
Current	4A continuous
Other	Overvoltage protection. Filtered and regulated

Battery Charging

Capacity	12VDC/7AH (2 within enclosure) 40AH/65AH(requires separate enclosure)
----------	--

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous

Batteries are sold separately

Supervision

AC Failure	Form "C" contacts
Battery	Form "C" contacts

Low DC Power Shutdown

Shuts down DC output terminals if battery voltage drops below
70-75% for 24V units (depending on the power supply)
Prevents deep battery discharge

Indicators (LED)

Input	120VAC is present
DC Output	Powered
Battery	Discharged or not connected

Power Distribution Module (PD8UL):**Input**

Voltage	24VDC from eFlow4NB
---------	---------------------

Outputs

Voltage	24VDC
Output Fuses	3.5A/250V

Indicators (LED)

Green LED	DC Output
-----------	-----------

TM400K6 Kit:**Agency Listings**

CE	European Conformity
----	---------------------

Physical and Environmental**Dimensions (H x W x D)**

Enclosure:
15.5" x 12.23" x 4.5" (393.7mm x 310.6mm x 114.3mm)

Shipping:
16.5" x 13.5" x 6" (419.1mm x 342.9mm x 152.5mm)

Weight (approx.)

Product	8.75 lb. (3.97 kg)
Shipping	10.0 lb. (4.5 kg)

Temperature


Operating	0°C to 49°C (32°F to 120°F)
Storage	- 20°C to 70°C (- 4°F to 158°F)

Relative Humidity	20 to 85%, non-condensing
-------------------	---------------------------

BTU/Hr (approx.):	49 BTU/Hr.
-------------------	------------

Access Controller Position Chart for the Following Models:

Mercury	Pem Mounting
MR50	(A)
LP1502, LP4502, MR52, MR16IN, MR16OUT	(B)



Dimensions and Drawing

Dimensions (H x W x D approximate)

15.5" x 12.23" x 4.5" (393.7mm x 310.6mm x 114.3mm)

