


Tempo724Q

Two Channel Networked Annual Event Timer



Altronix Tempo724Q Network Timer is designed to support a wide range of applications such as Home and Building Automation, Security, Access Control, Lighting Control, and more. Tempo724Q is equipped with two independently controlled form “C” relay contacts that provides many latching and/or momentary operations during a program schedule of your choice. LINQ™ Network management technology allows for remote control, programming, and reporting of diagnostics via Email/Dashboard. Events may be set for single or multiple operations on a daily and/or weekly schedule.



Tempo724Q

Specifications

Input

Voltage	12VDC/24VDC operation or PoE (12.95W, Class 3)
Aux	12V 100mA, 24 V 80mA

Relays

Contact Rating	Form “C” 5A 24VDC/120VAC
Standby Current	10mA (relay off) or 50mA (relay on)

Timer Features

- Flash memory protects against loss of programming due to power failure
- Accurate crystal controlled clock
- Momentary and/or Latching Events
- 60 individually programmed daily/weekly events
- Block programming capacity can accommodate a total of 420 events per week
- 30 programmable Holiday dates
- Automatic compensation for leap year

Timer Alerts

- System Start up
- “First man in” option
 - FM1 Active / Inactive
 - FM2 Active / Inactive
- Standard or Daylight Savings Time settings
 - Enabled / Disabled
- Relays
 - Relay Channel 1: On/Off
 - Relay Channel 2: On/Off
- Trigger Inputs (Programmed, relay does not change state)*
 - Trigger 1 Active / Inactive
 - Trigger 2 Active / Inactive

* Reserved for future use

Indicators (LED)

- PoE input
- AUX power input
- Battery LED
- Heartbeat (flashing)

Embedded LINQ™ Network Management Technology

- Remote programming
- Programmable users
- USB Network programming
- Email and dashboard alerts

Battery Charging

Type	Sealed lead acid or gel type
Current	0.25A
Failover	Upon AC loss, instantaneous

Physical and Environmental

Dimensions (L x W x H)

- Board: 5.5" x 3.5" x 1" (127mm x 98.9mm x 25.4mm)
- Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

Weight (approx.)

Product:	0.48 lb. (0.22 kg)
Shipping:	0.5 lb. (0.23 kg)

Temperature

Operating:	– 20°C to 49°C (– 4°F to 120°F)
Storage:	– 25°C to 70°C (– 13°F to 158°F)

Relative Humidity 85% +/- 5%

Mounting hardware is included

Lifetime Warranty


Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com

Dimensions and Drawing

Board Dimensions (L x W x H approximate)

5.5" x 3.5" x 1" (127mm x 98.9mm x 25.4mm)

**Lifetime Warranty**

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com