

Trove3

Versatile Access & Power Integration Enclosure

Description

Altronix Trove3 can house Altronix backplanes which accommodate various combinations of access controllers and accessories from the industry's leading manufacturers with or without Altronix power supplies and accessories for access systems. Trove systems simplify board layout and wire management, reducing installation time and labor costs.



Trove3

Specifications

Features

- 19 AWG powder coated steel.
- Convenient knockout configuration:
 - Single 2.415" diameter knockout located top of enclosure.
 - Two (2) double knockouts (1.948" and 1.5").
 - Thirteen (13) double knockouts (1.115" and 1.362").
- Includes cam lock, tamper switch and mounting hardware.

Agency Listings

- UL: UL294 - Access Control System.
- cUL: CAN/ULC - s319-05 - Electronic Access Control Systems.
- CE European Conformity

Capacity

- Accommodates up to four (4) 12VDC/12AH batteries.

Physical and Environmental

Dimensions (H x W x D)

36.12" x 30.125" x 7.06" (917.5mm x 768.1mm x 179.3mm).

Product Weight 60 lb. (27.22 kg).

Shipping Weight 65 lb. (29.5 kg).

Optional Backplanes

Backplane Model	Backplane with Enclosure Model	Manufacturer	Dimensions (H x W x D)
TBL3	TROVE3BL3	Universal Blank Backplane	34.0" x 28.0" x 0.3125" (863.6mm x 711.2mm x 7.9mm)
TCV3	TROVE3CV3	CDVI	
THW3	TROVE3HW3	Honeywell	
TM3	TROVE3M3	Mercury	
TSH3	TROVE3SH3	Software House	
TV3	TROVE3V3	HID Vertx	

Trove3

Versatile Access & Power Integration Enclosure

Dimensions and Drawing

Dimensions (H x W x D approximate)
 36.12" x 30.125" x 7.06" (917.5mm x 768.1mm x 179.3mm)

