

VB6

Power Supply

Altronix VB6 is a cost-effective 56VDC/30W UL Listed limited power supply. It is intended to power PoE related products such as the CAT5 to Coax cable Managed Ethernet Midspan receiver eBridge4PCRX and the transceiver with integral managed PoE/PoE+ switch eBridge4SK. VB6 provides two sets of output terminals to facilitate connection for up to two devices. It is powered by a 24VAC/24VDC Class 2 rated transformer/power supply.



VB6

Specifications

Input

Voltage 24VAC @ 1.5A or 24VDC @ 1.5A

Output

Voltage Two (2) 56VDC outputs with up to 30W combined total power

Other Built-in overload protection
Filtered and regulated

Indicators (LED)

Input and Output LEDs

Agency Listings

UL/cUL: Information Technology Equipment
(UL 60950-1)

cUL: CSA Standard C22.2 No.205-M1983,
Signal Equipment

CE European Conformity

Physical and Environmental

Dimensions (L x W x H)

Enclosure: 3.5" x 3.5" x 1" (88.9mm x 88.9mm x 25.4mm)

Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

Weight (approx.)

Product Weight: 0.25 lb. (0.11 kg)

Shipping Weight: 0.3 lb. (0.14 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)

Storage: -20°C to 70°C (-4° to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 15 BTU/Hr.

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com