

VB9P

Voltage Booster/Converter

Altronix VB9P converts a 24VDC input into 54VDC/90W output(s), intended to power PoE related products such midspans, receivers, adapters, and accessories. VB9P provides two sets of output terminals to facilitate connection for up to two devices.



Specifications

Input

Voltage 24VDC @ 4A

Output

Voltage Two (2) 54VDC outputs with up to 90W combined total power

Other Built-in overload protection
Filtered and regulated

Indicators (LED)

Output LED

Agency Listings

CE European Conformity

Physical and Environmental

Dimensions (L x W x H)

Enclosure: 3.5" x 3.5" x 1" (88.9mm x 88.9mm x 25.4mm)

Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

Weight (approx.)

Product Weight: 0.25 lb. (0.11 kg)

Shipping Weight: 0.3 lb. (0.14 kg)

Temperature

Operating: 0°C to 70°C (32°F to 158°F)


Storage: -20°C to 70°C (-4° to 158°F)

Relative Humidity 85% +/- 5%

Operating Altitude -304.8 to 3,048m

BTU/Hr. (approx.): 15 BTU/Hr.

Accessories



DCL2 - DIN Rail Mounting Clip

Allows for easy installation of Altronix adapters utilizing screw mounting holes to mount on a standard DIN rail (Altronix Din Rail models D10, D12, D19, or D24).

DCL2

Lifetime Warranty