

## VR1TM5

### Voltage Regulator

Altronix VR1TM5 converts a 24VAC or 24VDC input into a regulated 5VDC output. It provides power for 5VDC accessories, REX PIR's, Prox Readers, etc. Quick release terminals facilitate ease of wiring. Compact design allows for integration in a wide range of camera housings.



VR1TM5

### Specifications

#### Input

Voltage 24VAC or 24VDC

#### Output

Voltage 5VDC  
 Current 1A continuous supply current  
 Other Built-in overload protection  
 Filtered and regulated

#### Indicators (LED)

Input LED

#### Agency Listings

CE European Conformity

### Physical and Environmental

#### Dimensions (L x W x H)

Enclosure: 2.375" x 1.625" x 1" (60mm x 41mm x 25mm)  
 Shipping: 8" x 6" x 5" (203.2mm x 152.4mm x 127mm)

#### Weight (approx.)

Product Weight: 0.14 lb. (0.06 kg)  
 Shipping Weight: 0.3 lb. (0.14 kg)

#### Temperature

Operating: 0°C to 49°C (32°F to 120°F)  
 Storage: -20°C to 70°C (-4° to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 3 BTU/Hr.

### Lifetime Warranty