

VertiLineD Series

Sixteen (16) Output CCTV DC Rack Mount Power Supplies

Altronix VertiLine Rack Mount Power Supplies provide sixteen (16) filtered and electronically regulated power outputs in a space saving 1U EIA 19" rack mount chassis. The units are available with either 12VDC or 24VDC power outputs.

VERTILINE™


VertiLine33D

Key Features

- 115VAC input
- Sixteen (16) PTC protected outputs
- 12VDC (VertiLine33(T)D) or 24VDC (VertiLine63(T)D) PTC outputs
- Surge protection
- Individual power LED indicators
- Illuminated power disconnect circuit breaker with manual reset
- Removable terminal blocks with locking screw flanges
- CE European Conformity
- Lifetime Warranty

VertiLineD Series Configuration Reference Chart

Altronix Model Number	115VAC 60Hz Input Current	Output Voltage (VDC)	Total Output Current (Power)	Number of Outputs	Current (max. per output)	Output PTC Rating
VertiLine33D	1.5A	12VDC	8A	16	2.5A	2.5A
VertiLine33TD	3A		16A			
VertiLine63D	3A	24VDC	8A			
VertiLine63TD	6A		16A			

Specifications

Input

Voltage 115VAC, 60Hz

Output

Sixteen (16) PTC protected power outputs

Voltage

VertiLine33D, VertiLine33TD: 12VDC

VertiLine63D, VertiLine63TD: 24VDC

Other

Short circuit and thermal overload protection
Filtered and regulated

Indicators (LED)

Master Illuminated master power disconnect circuit breaker with manual reset

Output Sixteen (16) individual LEDs

Agency Listings

CE European Conformity

Physical and Environmental

Dimensions (H x W x D)

Modular 1U standard EIA 19" rack mount chassis

1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
VertiLine33D	7.2 lb. (3.27 kg)	8.3 lb. (3.76 kg)
VertiLine33TD	7.95 lb. (3.61 kg)	9.05 lb. (4.11 kg)
VertiLine63D	7.2 lb. (3.27 kg)	8.3 lb. (3.76 kg)
VertiLine63TD	7.95 lb. (3.61 kg)	9.05 lb. (4.11 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.):

VertiLine33D: 49 BTU/Hr.	VertiLine63D: 98 BTU/Hr.
VertiLine33TD: 98 BTU/Hr.	VertiLine63TD: 197 BTU/Hr.

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com