

VertiLine33TDV -**Rack Mount DC Power Supply**

Description

Specifications

Altronix Vertiline33TDV Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated auto-resettable power outputs in a space saving 1U EIA 19" rack mount chassis.



- Specifications			
Input Voltage	220VAC, 50/60Hz, 1.5A.	Agency Listings CE European Conformity.	
Output Voltage Current Fusing	12VDC. 16A max. total supply currect. Individual outputs' PTCs rated @ 2.5A.	 Physical and Environmental Dimensions (H x W x D) 1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm). Product Weight 7.95 lbs. (3.61 kg). Shipping Weight 9.05 lbs. (4.11 kg). Temperature 	
Other	Short circuit and thermal overload protection. Filtered and regulated.		
Indicators (LED) Master Output	Illuminated master power disconnect circuit breaker with manual reset. Sixteen (16) individual LEDs.	Operating Storage Relative Humidity BTU/Hr. (approx.):	0°C to 49°C (32°F to 120°F). -20°C to 70°C (-4°F to 158°F). 85% +/-5%. 98 BTU/Hr.



Altronix Rev. VertiLine33TDV-05242017