

VertiLine6DV

Rack Mount DC Power Supply

Altronix Vertiline6DV Rack Mount DC Power Supply provides eight (8) filtered and electronically regulated auto-resettable power outputs in a space saving 1U EIA 19" rack mount chassis.




VertiLine6DV

Specifications

Input

Voltage 220VAC (working range 190VAC - 256VAC),
50/60Hz, 0.75A.

Output

Voltage 24VDC.
Current 8A max. total supply current.
Fusing Individual outputs' PTCs rated @ 2.5A.
Other Short circuit and thermal overload protection.
Filtered and regulated.

Indicators (LED)

Master Illuminated master power disconnect
circuit breaker with manual reset.
Output Eight (8) individual LEDs.

Agency Listings

CE European Conformity.

Physical and Environmental

Dimensions (H x W x D)
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).
Product Weight 8.0 lb. (3.63 kg).
Shipping Weight 9.3 lb. (4.22 kg).
Temperature
Operating 0°C to 49°C (32°F to 120°F).
Storage - 20°C to 70°C (- 4°F to 158°F).
Relative Humidity 85% +/- 5%.
BTU/Hr. (approx.): 98 BTU/Hr.

Lifetime Warranty