

WPTV244220 Series

AC CCTV Outdoor Power Supplies

Altronix WPTV244220 Series Outdoor CCTV Power Supplies provide 24VAC or 28VAC distributed via four (4) outputs for powering CCTV cameras, heaters, and other video accessories.



WPTV244300220


Key Features

- NEMA 4 Rated enclosure for outdoor use
- Four (4) outputs:
 - One (1) fuse protected output
 - Three (3) PTC protected outputs rated @ 2.5A
- 24VAC or 28VAC supply current
- Surge protection
- AC Power LED
- Illuminated power disconnect circuit breaker with manual reset
- Spare fuses provided (all models with primary and/or secondary fuses)
- CE European Conformity
- Lifetime Warranty

WPTV244220 Series Power Supply Configuration Reference Chart

Altronix Model Number	Total Output Current (Power)	Output Voltage	Number of Outputs	PTC Protected Outputs (auto-resettable)	Output Current (max. per output) PTC Protected	Fuse Protected Outputs	Fuse Protected Output Rating	220VAC, 50/60Hz Input Current
WPTV244175220	7.25A	24VAC	4	3	2.5A (1A per output max)	1	10A/250VA	0.8A
	6.25A	28VAC						
WPTV244300220	12.5A	24VAC						
	10A	28VAC						

Accessories (order separately)



PMK1 - Pole Mount Kit

PMK1 pole mount kit is designed to simplify installation of outdoor units. It accommodates 2" - 8" (diameter) poles.

Lifetime Warranty



WPTV244220 Series

AC CCTV Outdoor Power Supplies

Specifications

Input

Voltage 220VAC (working range 198VAC - 256VAC), 50/60Hz

Current Varies, see Reference Chart

Outputs

Voltage 24VAC or 28VAC

Current Varies, see Reference Chart

Protection One (1) fuse protected output
Three (3) PTC protected outputs

Indicators (LED)

Input AC is present

Agency Listings

CE European Conformity

Physical and Environmental

NEMA 4 Rated enclosure for outdoor use

Dimensions (H x W x D)

Enclosure:

12" x 8" x 6" (304.8mm x 203.2mm x 152.4mm)

Shipping:

18" x 14" x 10" (457.2mm x 355.6mm x 254mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
WPTV244175220	15.2 lb. (6.9kg)	16.4 lb. (7.44 kg)
WPTV244300220	18.15 lb. (8.23 kg)	19.4 lb. (8.8 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)

Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr (approx.)

Model	24VAC	28VAC
WPTV244175220	86	90
WPTV244300220	114	106

Lifetime Warranty