

WayPoint10A

Outdoor AC Power Supply

Altronix WayPoint10A Outdoor Power Supply provides 24VAC and/or 28VAC distributed via two outputs for powering CCTV cameras, heaters, and other video accessories. It is designed to be conveniently located where power is required. Lightweight molded fiberglass reinforced polyester enclosure is NEMA 4/4X, IP66-11 Rated for outdoor use. It features lockable stainless steel latches and integral flanges to simplify wall or pole mounting.



WAYF

WayPoint10A

┌ Specifications				
Input		Physical and Enviro	Physical and Environmental	
Voltage	115VAC, 50/60Hz, 1.2A or		Dimensions (H x W x D)	
	230VAC, 50/60Hz, 0.7A	Enclosure:	$= 50^{\circ} (220.1 \text{ mm y } 207.2 \text{ mm y } 142 \text{ mm})$	
Output Optionsa. 24VAC @ 4A max.b. 28VAC @ 3.5A max.c. Both 24VAC and 28VAC, not to exceed 3.5A max.Fuse Ratings5A /250V		Shipping: 20.25" x 12.5" x 7	20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm) NEMA 4/4X, IP66-11 Rated enclosure for outdoor use Weight (approx.) Product: 11.8 lb. (5.35 kg)	
Indicators (LED) Individual power output LED indicators Illuminated master power switch		Temperature Operating: Storage:	- 20°C to 50°C (- 4°C to 122°F) - 40°C to 70°C - 40°C to 158°F)	
Agency Listings CE	European Conformity	Relative Humidity BTU/Hr. (approx.):		

Accessories (order separately)



PMK1 -Pole Mount Kit

PMK1 pole mount kit is designed to simplify installation of outdoor units. It accommodates 2"- 8"(diameter) poles. Rev. 09122022



WayPoint10A

Outdoor AC Power Supply

Dimensions and Drawing

Dimensions (H x W x D approximate)

13.31" x 11.31" x 5.59" (338.1mm x 287.3mm x 142mm)





