


# eFlow104NB

## Power Supply/Charger

### Description

Altronix eFlow104NB UL Listed Sub-Assembly power supply/charger converts a 120VAC, 60Hz input into a single 24VDC output. It also offers a suite of features that includes fire alarm disconnect, overvoltage protection, and low power disconnect which prevents deep discharge of stand-by batteries.



eFlow104NB

### Specifications

#### Input

Voltage	120VAC, 60Hz, 4.5A max.
Fusing	6.3A / 250V.

#### Outputs

Voltage	24VDC.
Current	10A continuous max.
Auxiliary	Power-limited @ 1A (unswitched).
Other	Overvoltage protection. Filtered and regulated.

#### Back-up Battery *(not included)*

Type	Sealed lead acid or gel type.
Fuse Rating	15A @ 32VDC.
Failover	Upon AC loss, instantaneous.

#### Fire Alarm Disconnect

Supervised	Latching or non-latching.
EOL	10K Resistor.

#### Supervision

AC Failure	Form "C" contacts.
Battery	Form "C" contacts.

#### Low DC Power Shutdown

Shuts down DC output terminals if battery voltage drops below 71-73% for 12V units and 70-75% for 24V units (depending on the power supply). Prevents deep battery discharge.

#### Indicators (LED)

Input	120VAC is present.
DC Output	Powered.

#### Agency Listings

<b>UL:</b>	
Access Control	UL294
Burglar Alarm	UL603
Fire Alarm	UL1481
<b>cUL:</b>	
Burglar Alarm	ULC-S318-96
Access Control	ULC-S319-05
Signal Equipment	CSA C22.2 No.205

#### Physical and Environmental

<b>Dimensions (L x W x H)</b>	
8.25" x 4.56" x 1.5" (209.5 mm x 115.8 mm x 38.1 mm).	
<b>Product Weight</b>	1.1 lbs. (0.5 kg).
<b>Shipping Weight</b>	1.25 lbs. (0.57 kg).
<b>Temperature</b>	
Operating	0°C to 49°C (32°F to 120°F).
Storage	-20°C to 70°C (-4°F to 158°F).
<b>Relative Humidity</b>	85% +/-5%.
<b>BTU/Hr. (approx.):</b>	123 BTU/Hr.

### Accessories

#### Network Supervision

Altronix model LINQ2 Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Reports system diagnostics via Email





# eFlow104NB Power Supply/Charger

## Board Dimensions (L x W x H) and Drawing

8.25" x 4.56" x 1.5" (209.5 mm x 115.8 mm x 38.1 mm)

